

**PART 13 – UNITS OF MEASUREMENT
TO BE USED IN AIR AND GROUND OPERATIONS**

13.1 GENERAL

13.1.1 General

13.1.1.1 APPLICABILITY

The Standards contained in this Regulation shall be applicable to all aspects of international civil aviation air and ground operations Within the Kingdom of Cambodia and the airspace controlled by Cambodia.

13.1.1.2 DEFINITIONS

For the purpose of Part 13, the following definitions shall apply—

Ampere (A). The ampere is that constant electric current which, if maintained in two straight parallel conductors of infinite length, of negligible circular cross-section, and placed 1 metre apart in vacuum, would produce between these conductors a force equal to 2 x newton per metre of length.

Becquerel (Bq). The activity of a radionuclide having one spontaneous nuclear transition per second.

Candela (cd). The luminous intensity, in the perpendicular direction, of a surface of 11600 000 square metre of black body at the temperature of freezing platinum under a pressure of 101 325 newtons per square metre.

Celsius temperature (t_c). The Celsius temperature is equal to the difference $t_c = T - T_0$ between two thermodynamic temperatures T and T₀ where T₀ equals 273.15 kelvin.

Coulomb (C). The quantity of electricity transported in 1 second by a current of 1 ampere.

Degree Celsius (°C). The special name for the unit kelvin for use in stating values of Celsius temperature.

Farad (F). The capacitance of a capacitor between the plates of which there appears a difference of potential of 1 volt when it is charged by a quantity of electricity equal to 1 coulomb.

Foot Cft). The length equal to 0.304 8 metre exactly.

Gray (Gy). The energy imparted by ionizing radiation to a mass of matter corresponding to 1 joule per kilogram.

Henry (H). The inductance of a closed circuit in which an electromotive force of 1 volt is produced when the electric current in the circuit varies uniformly at a rate of 1 ampere per second.

Hertz (Hz). The frequency of a periodic phenomenon of which the period is 1 second.

Human performance. Human capabilities and limitations which have an impact on the safety and efficiency of aeronautical operations.

Joule (J). The work done when the point of application of a force of 1 newton is displaced a distance of 1 metre in the direction of the force.

Kelvin (K). A unit of thermodynamic temperature which is the fraction $\frac{1}{273.15}$ of the thermodynamic temperature of the triple point of water.

Kilogram (kg). The unit of mass equal to the mass of the international prototype of the kilogram.

Knot (kt). The speed equal to 1 nautical mile per hour.

Litre (L). A unit of volume restricted to the measurement of liquids and gases which is equal to 1 cubic decimetre.

Lumen (lm). The luminous flux emitted in a solid angle of 1 steradian by a point source having a uniform intensity of 1 candela.

Lux (Lr). The illuminance produced by a luminous flux of 1 lumen uniformly distributed over a surface of 1 square metre.

Metre (m). The distance travelled by light in a vacuum during $\frac{1}{299\,792\,458}$ of a second.

Mole (mol). The amount of substance of a system which contains as many elementary entities as there are atoms in 0.012 kilogram of carbon-12.

Note.- When the mole is used, the elementary entities must be specified and may be atoms, molecules, ions, electrons, other particles or specified groups of such particles.

Nautical mile (NM). The length equal to 1 852 metres exactly.

Newton (N). The force which when applied to a body having a mass of 1 kilogram gives it an acceleration of 1 metre per second squared.

Ohm (Ω). The electric resistance between two points of a conductor when a constant difference of potential of 1 volt, applied between these two points, produces in this conductor a current of 1 ampere, this conductor not being the source of any electromotive force.

Pascal (Pa). The pressure or stress of 1 newton per square metre.

Radian (rad). The plane angle between two radii of a circle which cut off on the circumference an arc equal in length to the radius.

Second (s). The duration of $9\,192\,631\,770$ periods of the radiation corresponding to the transition between the two hyperfine levels of the ground state of the caesium-133 atom.

Siemens (S). The electric conductance of a conductor in which a current of 1 ampere is produced by an electric potential difference of 1 volt.

Sievert (Sv). The unit of radiation dose equivalent corresponding to 1 joule per kilogram.

Steradian (sr). The solid angle which, having its vertex in the centre of a sphere, cuts off an area of the surface of the sphere equal to that of a square with sides of length equal to the radius of the sphere.

Tesla (T). The magnetic flux density given by a magnetic flux of 1 weber per square metre.

Tonne (t). The mass equal to 1 000 kilograms.

Volt (V). The unit of electric potential difference and electromotive force which is the difference of electric potential between two points of a conductor carrying a constant current of 1 ampere, when the power dissipated between these points is equal to 1 watt.

Watt (W). The power which gives rise to the production of energy at the rate of 1 joule per second.

Weber (Wb). The magnetic flux which, linking a circuit of one turn, produces in it an electromotive force of 1 volt as it is reduced to zero at a uniform rate in 1 second.

13.2 STANDARD APPLICATION OF UNITS AND MEASUREMENT

13.2.1 SI Units

13.2.1.2 APPLICABILITY

The International System of Units developed and maintained by the General Conference of Weights and Measures (CGPM) shall, subject to the provisions of 13.2.2 and 13.2.3, be used as the standard system of units of measurement for all aspects of international civil aviation air and ground operations in Cambodia and Cambodian controlled airspace.

13.2.1.3 PREFIXES

The prefixes and symbols listed in Table 2-1 shall be used to form names and symbols of the decimal multiples and sub-multiples of SI units.

Note 1.- As used herein the term SI unit is meant to include base units and derived units as well as their multiples and sub-multiples.

Note 2: See Attachment B of ICAO Annex 5 for guidance on the general application of prefixes .

13.2.2 Non-SI Units

13.2.2.1 NON-SI UNITS FOR PERMANENT USE WITH THE SI

The non-SI units listed in Table 2-2 shall be used either in lieu of, or in addition to, SI units as primary units of measurement but only as specified in Table 2-4.

13.2.2.2 NON-SI ALTERNATIVE UNITS PERMITTED FOR TEMPORARY USE WITH THE SI

The non-SI units listed in Table 2-3 shall be permitted for temporary use as alternative units of measurement but only for those specific quantities listed in Table 2-4.

Note: It is intended that the use of the non-SI alternative units listed in Table 2-3 and applied as indicated in Table 2-4 will eventually be discontinued in accordance with individual unit termination dates established by the Council of ICAO. Termination dates, when established, will be made Standards (see chapter 13.3)

Table 2-1. SI unit prefixes

Multiplication factor		Prefix	Symbol
1 000 000 000 000 000 000 =	10^{18}	exa	E
1 000 000 000 000 000 =	10^{15}	peta	P
1 000 000 000 000 =	10^{12}	tera	T
1 000 000 000 =	10^9	giga	G
1 000 000 =	10^6	mega	M
1 000 =	10^3	kilo	k
100 =	10^2	hecto	h
10 =	10^1	deca	da
0.1 =	10^{-1}	deci	d
0.01 =	10^{-2}	centi	c
0.001 =	10^{-3}	milli	m
0.000 001 =	10^{-6}	micro	μ
0.000 000 001 =	10^{-9}	nano	n
0.000 000 000 001 =	10^{-12}	pico	p
0.000 000 000 000 001 =	10^{-15}	femto	f
0.000 000 000 000 000 001 =	10^{-18}	atto	a

13.2.3 Application of specific units

13.2.1.3 APPLICABILITY

The application of units of measurement for certain quantities used in international civil aviation air and ground operations shall be in accordance with Table 2-4.

Note: Table 2-4 is intended to provide standardization of units (including prefixes) for those quantities commonly used in air and ground operations. Basic provisions of this Regulation apply for units to be used for quantities not listed.

13.2.3.2 RECOMMENDATION-

Means and provisions for design, procedures and training should be established for operations in environments involving the use of standard and non-SI alternatives of specific units of measurement, or the transition between environments using different units, with due consideration to human performance

Note: Guidance material on human performance is provided by ICAO in the Human Factors Training Manual (Doc 9683) and Circular 238 (Human Factors Digest No. 6 - Ergonomics).

Table 2-2. Non-SI units for use with the SI

<i>Specific quantities in Table 2-4 related to</i>	<i>Unit</i>	<i>Symbol</i>	<i>Definition (in terms of SI units)</i>
mass	tonne	t	1t = 10 ³ kg
plane angle	degree	°	1° = (π/180) rad
	minute	'	1' = (1/60)° = (π/10 800) rad
	second	"	1" = (1/60)' = (π/648 000) rad
temperature	degree Celsius	°C	1 unit °C = 1 unit K ^{a)}
time	minute	min	1min=60s
	hour	h	1 h = 60 min = 3 600 s
	day	d	1 d = 24 h = 86 400 s
	week, month, year	—	
volume	litre	L	1 L = 1 dm ³ = 10 ⁻³ m ³

a) See Attachment C of ICAO Annex 5, Table C-2 for conversion.

Table 2-3. No1141 alternative units permitted for temporary use with the SI

<i>Specific quantities in Table 2-4 related to</i>	<i>Unit</i>	<i>Symbol</i>	<i>Definition (in terms of SI units)</i>
distance (long)	tonne	t	1t = 10 ³ kg
distance (vertical) ^{a)}	degree	°	1° = (π/180) rad
speed	minute	'	1' = (1/60)° = (π/10 800) rad

a) altitude, elevation, height, vertical speed.

Table 2-4. Standard application of specific units of measurement

<i>Ref. No.</i>	<i>Quantity</i>	<i>Primary unit (symbol)</i>	<i>Non-SI alternative unit (symbol)</i>
1. Direction, Space, Time			
1.1	altitude	m	ft
1.2	area	m ²	
1.3	distance (long) ^{a)}	km	NM
1.4	distance (short)	m	
1.5	elevation	m	ft
1.6	endurance	h and min	
1.7	height	m	ft
1.8	latitude	° ' "	
1.9	length	m	
1.10	longitude	° ' "	
1.11	plane angle (when required, decimal subdivisions of the degree shall be used)	°	
1.12	runway length	m	
1.13	runway visual range	m	
1.14	tank capacities (aircraft) ^{b)}	L	
1.15	time	s min h d week month year	
1.16	visibility ^{c)}	km	
1.17	volume	m ³	
1.18	wind direction (wind directions other than for a landing and take-off shall be expressed in degrees true; for landing and take-off wind directions shall be expressed in degrees magnetic)	°	
2. Mass related			
2.1	air density	kg / m ³	
2.2	area density	kg / m ²	
2.3	cargo capacity	kg	
2.4	cargo density	kg / m ³	
2.5	density (mass density)	kg / m ³	
2.6	fuel capacity (gravimetric)	kg	
2.7	gas density	kg / m ³	
2.8	gross mass or payload	kg t	
2.9	hoisting provisions	kg	
2.10	linear density	kg / m	
2.11	liquid density	kg / m ³	
2.12	mass	kg	
2.13	moment of inertia	kg · m ²	
2.14	moment of momentum	kg · m ² /s	
2.15	momentum	kg · m / s	

<i>Ref. No.</i>	<i>Quantity</i>	<i>Primary unit (symbol)</i>	<i>Non-SI alternative unit (symbol)</i>
3. Force related			
3.1	air pressure (general)	kPa	
3.2	altimeter setting	hPa	
3.3	atmospheric pressure	hPa	
3.4	bending moment	kN·m	
3.5	force	N	
3.6	fuel supply pressure	kPa	
3.7	hydraulic pressure	kPa	
3.8	modulus of elasticity	MPa	
3.9	pressure	kPa	
3.10	stress	MPa	
3.11	surface tension	mN/m	
3.12	thrust	kN	
3.13	torque	N · m	
3.14	vacuum	Pa	
4. Mechanics			
4.1	Airspeed ^{d)}	km/h	Kt
4.2	angular acceleration	rad/s ²	
4.3	angular velocity	rad/s	
4.4	energy or work	J	
4.5	equivalent shaft power	kW	
4.6	frequency	Hz	
4.7	ground speed	km/h	Kt
4.8	impact	J/m ²	
4.9	kinetic energy absorbed by brakes	MJ	
4.10	linear acceleration	m/s ²	
4.11	power	kW	
4.12	rate of trim	°/s	
4.13	shaft power	kW	
4.14	velocity	m/s	
4.15	vertical speed	m/s	
4.16	wind speed	km/h	Kt
5. Flow			
5.1	engine airflow	kg/s	
5.2	engine waterflow	kg/h	
5.3	fuel consumption (specific)		
	piston engines	kg/(kW · h)	
	turbo-shaft engines	kg/(kW · h)	
	jet engines	kg/(kN · h)	
5.4	fuel flow	kg/h	
5.5	fuel tank filling rate (gravimetric)	kg/min	
5.6	gas flow	kg/s	
5.7	liquid flow (gravimetric)	g/s	
5.8	liquid flow (volumetric)	L/s	
5.9	mass flow	kg/s	
5.10	oil consumption		
	gas turbine	kg/h	
	piston engines (specific)	g/(kW · h)	

<i>Ref. No.</i>	<i>Quantity</i>	<i>Primary unit (symbol)</i>	<i>Non-SI alternative unit (symbol)</i>
5.11	oil flow	g/s	
5.12	pump capacity	L/min	
5.13	ventilation airflow	m ³ /min	
5.14	viscosity (dynamic)	Pa · s	
5.15	viscosity (kinematic)	m ² /s	
6. Thermodynamics			
6.1	coefficient of heat transfer	W/(m ² · K)	
6.2	heat flow per unit area	J/m ²	
6.3	heat flow rate	W	
6.4	humidity (absolute)	g/kg	
6.5	coefficient of linear expansion	°C ⁻¹	
6.6	quantity of heat	J	
6.7	temperature	°C	
7. Electricity and magnetism			
7.1	capacitance	F	
7.2	conductance	S	
7.3	conductivity	S/m	
7.4	current density	A/m ²	
7.5	electric current	A	
7.6	electric field strength	C/m ²	
7.7	electric potential	V	
7.8	electromotive force	V	
7.9	magnetic field strength	A/m	
7.10	magnetic flux	Wb	
7.11	magnetic flux density	T	
7.12	power	W	
7.13	quantity of electricity	C	
7.14	resistance	Ω	
8. Light and related electromagnetic radiations			
8.1	illuminance	lx	
8.2	luminance	cd/m ²	
8.3	luminous exitance	lm/m ²	
8.4	luminous flux	lm	
8.5	luminous intensity	cd	
8.6	quantity of light	lm · s	
8.7	radiant energy	J	
8.8	wavelength	m	
9. Acoustics			
9.1	frequency	Hz	
9.2	mass density	kg/m ³	
9.3	noise level	dB ^e)	
9.4	period, periodic time	s	
9.5	sound intensity	W/m ²	
9.6	sound power	W	
9.7	sound pressure	Pa	

<i>Ref: No.</i>	<i>Quantity</i>	<i>Primary unit (symbol)</i>	<i>Non-SI alternative unit (symbol)</i>
9.8	sound level	dB ^{e)}	
9.9	static pressure (instantaneous)	Pa	
9.10	velocity of sound	m/s	
9.11	volume velocity (instantaneous)	m ³ /s	
9.12	wavelength	m	
10. Nuclear physics and ionizing radiation			
10.1	absorbed dose	Gy	
10.2	absorbed dose rate	Gy/s	
10.3	activity of radionuclides	Bq	
10.4	dose equivalent	Sv	
10.5	radiation exposure	C/kg	
10.6	exposure rate	C/kg · s	

- a) As used in navigation, generally in excess of 4 000 m.
- b) Such as aircraft fuel, hydraulic fluids, water, oil and high pressure oxygen vessels.
- c) Visibility of less than 5 km may be given in m.
- d) Airspeed is sometimes reported in flight operations in terms of the ratio MACH number.
- e) The decibel (dB) is a ratio which may be used as a unit for expressing sound pressure level and sound power level. When used, the reference level must be specified.

13.3 TERMINATION OF USE OF NON-SI ALTERNATIVE UNITS

The non-SI units listed in Table 2-3 have been retained temporarily by ICAO for use as alternative units because of their widespread use and to avoid potential safety problems which could result from the lack of international coordination concerning the termination of their use. When termination dates will be established by the Council of ICAO, they will be reflected as Standards by the SSCA.

Note : the establishment of such termination dates by ICAO is expected to be well in advance of actual termination. Any special procedures associated with specific unit termination should be circulated to all States in due time.